

HEPAX Manual

Addendum Card

A few errors have unfortunately crept into the Owner's Manual for the HEPAX modules. Please correct with a pen.

Page Please correct:

- 8 Under the heading "Inserting and removing ...", please add the following paragraphs: "To minimize power consumed by the HEPAX module, insert it in port 1. Other configurations will reduce battery life slightly. Try to avoid placement in port 4. If the module is removed from your HP-41, it will lose its contents."
- 20 Please add a second paragraph under the heading "Transferring HEPAX files ...": "Almost full text files will be slightly expanded when transferred to mass storage by HWRTFL. If the file is already maximum size, or the HEPAX module is full, this may cause problems when retrieving the file using HREADFL."
- 20 The contents of the ALPHA register for the "HREADFL" function should be "Mass storage name, HEPAX name".
- 30 Line 47 of the "HRESZFL" program is illegible. It should read "47 FC? 00".
- 33 First word in third line from the bottom should be "HSEKPTA".
- 46 The "MYPRGM" program should read: LBL "MYPRGM", XF, 16, (needed SIZE), X <= Y?, GTO 00, ...
- 55 Please add "The test functions also work on ALPHA data."
- 55 Correct 6th line from bottom to "fig. 7 above."
- 67 The control word in line 7 is "000000eeeebbbb".
- 67 Line 18 of the "DISSST" program should read "18 DISASM".
- 71 Last line in second paragraph should read: "the last address that is changed (pushed down or pulled up)."
- 78 The control word in line 8 is "00bbbbeeeeeellll".

Page Please correct:

- 99 The register name of register 00Ah should read "┌" (the "append" character).
- 100 First sentence below fig. 14 should read "The first nibble is always a hexadecimal 1h, binary 0001b."
- 123 Add a footnote to the FETCH S&X instruction as follows: "Do no fetch from address 0002h, as this will cause a file system reset."
- 125 Correct 3rd word in 2nd last line from "write" to "read".
- 127 An "append" character (┌) is missing in lines 17, 22 and 42 of the "JUMP" program. These lines should read 17 "┌(space)", 22 "┌:" and 42 "┌,".
- 131 Following the first paragraph, please add: "Use PRPH SLCT with C[2:0] set to zero to deselect a peripheral."
- 135 An "append" character (┌) is missing in the parenthesis after the READ 10 and WRIT 10 instructions.
- 141 An "append" character (┌) is missing in the parenthesis after the WRIT 10 instruction.
- 167 An "append" character (┌) is missing in the parenthesis under parameter 10.
- 177 Correct the heading to "Batteries, Warranty and Service information". Add the following paragraph: "To avoid losing the contents of main, extended and HEPAX memory when changing the batteries, have the new batteries ready and complete the battery change within one minute."

If you have any suggestions for improving the HEPAX Module and/or the Owner's Manual, please let us know. Thank you.